



General information	
Product type designation	SM 1231, AI 4x16 bit RTD
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	40 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4; Resistance thermometer
permissible input voltage for voltage input (destruction limit), max.	±35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
• Voltage	No
• Current	No

- Thermocouple
- Resistance thermometer
- Resistance

No
 Yes; Resistance-type transmitter: Pt10, Pt50, Pt100, Pt200, Pt500, Pt1000, Ni100, Ni120, Ni200, Ni500, Ni1000, Cu10, Cu50, Cu100, LG-Ni1000
 Yes; 150 Ω, 300 Ω, 600 Ω

Input ranges (rated values), resistance thermometer

- Cu 10
 - Input resistance (Cu 10)
- Ni 100
 - Input resistance (Ni 100)
- Ni 1000
 - Input resistance (Ni 1000)
- LG-Ni 1000
 - Input resistance (LG-Ni 1000)
- Ni 120
 - Input resistance (Ni 120)
- Ni 200
 - Input resistance (Ni 200)
- Ni 500
 - Input resistance (Ni 500)
- Pt 100
 - Input resistance (Pt 100)
- Pt 1000
 - Input resistance (Pt 1000)
- Pt 200
 - Input resistance (Pt 200)
- Pt 500
 - Input resistance (Pt 500)

Yes
 10 Ω
 Yes
 100 Ω
 Yes
 1 000 Ω
 Yes
 1 000 Ω
 Yes
 120 Ω
 Yes
 200 Ω
 Yes
 500 Ω
 Yes
 100 Ω
 Yes
 1 000 Ω
 Yes
 200 Ω
 Yes
 500 Ω

Input ranges (rated values), resistors

- 0 to 150 ohms
- 0 to 300 ohms
- 0 to 600 ohms

Yes
 Yes
 Yes

Thermocouple (TC)

- Temperature compensation
 - parameterizable

No

Analog value generation for the inputs

Measurement principle integrating

Integration and conversion time/resolution per channel

- Resolution with overrange (bit including sign), max.
- Integration time, parameterizable

15 bit; + sign
 No



- Interference voltage suppression for interference frequency f1 in Hz

85 dB at 50 / 60 / 400 Hz

Errors/accuracies

Temperature error (relative to input range), (+/-) 25 °C ±0.1%, to 55 °C ±0.2% total measurement range

Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) 0.05 %

Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency

- Common mode interference, min. 120 dB

Interrupts/diagnostics/status information

Alarms Yes

Diagnostics function Yes; Can be read out

Alarms

- Diagnostic alarm Yes

Diagnoses

- Monitoring the supply voltage Yes
- Wire-break Yes

Diagnostics indication LED

- for status of the inputs Yes
- for maintenance Yes

Degree and class of protection

IP degree of protection IP20

Standards, approvals, certificates

CE mark Yes

CSA approval Yes

UL approval Yes

cULus Yes

FM approval Yes

RCM (formerly C-TICK) Yes

KC approval Yes

Marine approval Yes

Ambient conditions

Free fall

- Fall height, max. 0.3 m; five times, in product package

Ambient temperature during operation

- min. -20 °C
- max. 60 °C
- horizontal installation, min. -20 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -20 °C
- vertical installation, max. 50 °C

Ambient temperature during storage/transportation

• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Operation, min.	795 hPa
• Operation, max.	1 080 hPa
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
Relative humidity	
• Operation at 25 °C without condensation, max.	95 %
Pollutant concentrations	
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
Connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	220 g
last modified:	10/13/2020